



S-DIAL OUTDOOR

Controller 24 Vac

DESCRIPTION

S-Dial (Smart Dial) is a unique controller that bridges tradition to future.

Thanks to a graphic display is possible to see all the programs and the setting of the controller in a clear and user-friendly way. The controller has 4 programs and can be installed indoor or outdoor.

Using S-Dial it's possible to upgrade the functionality of the irrigation installation thanks to the fact that it is FLIWER COMPATIBLE.

It means that it is possible to connect S-Dial to a Fliwer Sensor or to a Link in order to manage remotely the irrigation and save water (at least 50%) through the Fliwer technology.

TECHNICAL CHARACTERISTICS

- 6 - 9 - 12 - 24 stations models
- Outdoor Model with Internal Transformer
- Electrical Power Supply: 220 VAC 50Hz
- Electrical Outputs: 24 Volts AC, 1.25 AMP
- 4 independent programs
- 4 independent start times
- Next start time visualization
- Run Times: 1 min. to 240 min per station
- Watering Schedule: 7 day calendar with individual day selection, or 1 to 19 day interval watering
- Water Budgeting Mode from 10% to 200%
- Master Valve/Pump 24 VAC outlet can be enabled or disabled by station
- Power Failure: 3V lithium battery permanently maintains programs
- Rain Sensor Inlet, programmable per each station
- Freeze-program function (OFF)
- 2.7" graphic colour display
- Low-battery function

1. 2.7" GRAPHIC COLOUR DISPLAY



2. SMART DIAL PROGRAMMING



Code	Models	Box Qt.y	Box - cm
200.5800600	S-DIAL 6 - 6 ZONES - 24 VAC - OUTDOOR	n.a.	n.a.
200.5800900	S-DIAL 9 - 9 ZONES - 24 VAC - OUTDOOR	n.a.	n.a.
200.5801200	S-DIAL 12 - 12 ZONES - 24 VAC - OUTDOOR	n.a.	n.a.
200.5802400	S-DIAL 24 - 24 ZONES - 24 VAC - OUTDOOR	n.a.	n.a.

